

INDUSTRIAL COMPONENT DATA

DMC 0,5/ 2-G1SH-2,54P20THR24 1097546 PHOENIX CONTACT

Printed circuit board base case, color: black, rated cu..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMC 0,5/ 2-G1SH-2,54P20THR24



Manufacturer	PHOENIX CONTACT
MPN / Reference	DMC 0,5/ 2-G1SH-2,54P20THR24
Catalog number	1097546
Category	Printed circuit board connector
Minimum order	300 Pcs
Document ID	EO-0B0C4FDCA9
Generated	2026-08-06

Product Overview

Printed circuit board base case, color: black, rated current: 5 A, rated voltage (III/2): 160 V, contact surface: Au, contact connection type: Male, number of poles: 2, item family: DMC 0,5/.. -G1-SH-THR, pitch: 2.54 mm, mounting: THR welding/wave welding, pin length [P]: 2 mm, plug-in system: COMBICON DFMC 0.5 shielded, Electrical properties: shielded, Plug-in face orientation: Standard, lock: shielded connection, fixing type: without, packaging type: 24 mm wide strap, Suitable for CAT 5

Base housing printed circuit board, color: black, rated current: 5 A, dimensioning voltage (III/2): 160 V, surface contacts: Gold, contact type: Male, Number of poles per row: 2, article family: DMC 0,5/.. -G1-SH-THR, pitch: 2.54 mm, pin length [P]: 2 mm, Stecksystem: MICRO COMBICON - DFMC 0.5 shielded, Electrical properties: shielded, Locking: shielded connection, packing type: 24 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

ETIM for 1097546 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Modular spacing contacts (EF007326)

2.54 mm

Modular spacing connections (EF006827)

2.54 mm

Rated current I_n (EF008250)

5 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Gold

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

2 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Black

Inflammability class of insulation material according to UL94 (EF002521)

V0

Type of fastening (EF002442)

Other

Type of banding (EF007011)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMC 0,5/ 2-G1SH-2,54P20THR24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.