


INDUSTRIAL COMPONENT DATA

DMC 1,5/13-G1F-3,5-LR P35 1053876 PHOENIX CONTACT

Housing base for printed circuit board, nominal current: 8..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMC 1,5/13-G1F-3,5-LR P35



Manufacturer	PHOENIX CONTACT
MPN / Reference	DMC 1,5/13-G1F-3,5-LR P35
Catalog number	1053876
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-C469F49225
Generated	2026-08-05

Product Overview

Housing base for printed circuit board, nominal current: 8 A, voltage and sizing (III/2): 160 V, number of poles: 13, pitch: 3.5 mm, color: green, surface of contact: Tin, assembly: wave Soldering

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 26, number of rows: 2, number of poles: 13, number of connections: 26, article family: DMC 1.5/.. -G1F, pitch: 3.5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, lock: Snap-in lock, fixing type: Lock & Release air clamping (thread), packaging type: boxed PCB base strip, nominal cross-section: 1.5 mm², colour: green, rated current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact type: pin, number of potentials: 26, number of rows: 2, number of poles: 13, number of terminals: 26, article family: DMC 1,5/.. -G1F, Pitch: 3.5 mm, Mounting: Wave Soldering, Pin Layout: Linear Pinning, Pin Length [P]: 3.5 mm, Number of Solder Pins per Potential: 1, Mating System: COMBICON DFMC 1.5, Mating Face Alignment: Standard, Locking: Lock and Release Latching, Mounting Type: Lock & Release Threaded Flange, Packaging Type: Packed in a Box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataItem propertiesProduct Type PCB Floor Strip

Product family DMC 1.5/.. -G1F

Product Line COMBICON Connectors S

Number of poles 13

Grid dimension 3.5 mm
Number of ports 26
Number of rows 2
Number of potentials 26
Pin layout Linear Pinning
Number of solder pins per potential 1
Data maintenance status
Article revision 00
Electrical propertiesNominal current I_N 8 A
Rated voltage U_N 160 V
Contact resistance 3 m?
Rated voltage (III/3) 160 V
Rated Surge Voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated Surge Voltage (III/2) 2.5 kV
Rated voltage (II/2) 250 V
Rated Surge Voltage (II/2) 2.5 kV
AssemblyMounting type Wave Soldering
Pin layout Linear Pinning
Flange
Tightening torque 0.2 Nm
Material specificationsMaterial information - Contact
Note WEEE/RoHS compliant, whisker-free according to IEC 60068-2-82/JEDEC JESD 201
Material Contact Cu alloy
Surface finish Electroplated
Metal Surface Contact Area (Top Layer) Tin (4 - 8 μ m Sn)
Metal Surface Contact Area (Interlayer) Nickel (1.5 - 4 μ m Ni)
Metal Surface Soldering Area (Top Layer) Tin (4 - 8 μ m Sn)
Metal Surface Soldering Area (Interlayer) Nickel (1.5 - 4 μ m Ni)
Material specifications - Housing
Color (Housing) Green (6021)
Insulating material PBT
Insulating material group IIIa
CTI according to IEC 60112 225
Flammability class according to UL 94 V0
DimensionsDimensional drawing
Grid dimension 3.5 mm
Width [w] 52.5 mm
Height [h] 14.3 mm
Length [l] 11.6 mm
Overall height 10.8 mm
Solder pin length [P] 3.5 mm
Pin Dime...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMC 1,5/13-G1F-3,5-LR P35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.