

## INDUSTRIAL COMPONENT DATA

# DMC 1,5/14-G2F-3,5-LR P20THR 1668698 PHOENIX CONTACT

## Printed circuit board base case, nominal section: 1.5 m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMC 1,5/14-G2F-3,5-LR P20THR



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | DMC 1,5/14-G2F-3,5-LR P20THR    |
| Catalog number  | 1668698                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-38BF6A7204                   |
| Generated       | 2026-08-05                      |

### Product Overview

DMC 1,5/14-G2F-3,5-LR P20THR 1668698 PHOENIX CONTACT Printed circuit board base case, nominal section: 1.5 m..

## STRUCTURED PRODUCT DATA

### Technical Specifications

| TECHNICAL ATTRIBUTE                       | VALUE           |
|-------------------------------------------|-----------------|
| Connector model (EF007495)                | Fixed connector |
| Contact type (EF001587)                   | Pin             |
| Number of plug-in contact rows (EF006935) | 2               |
| Modular spacing contacts (EF007326)       | 3.5 mm          |
| Modular spacing connections (EF006827)    | 3.5 mm          |
| Rated current In (EF008250)               | 8 A             |
| Rated voltage (EF000228)                  | 160 V           |
| Rated surge voltage (EF002993)            | 2.5 kV          |
| Over voltage category (EF006785)          | III             |
| Pollution degree (EF006786)               | 2               |
| Material of contact surface (EF004020)    | Tin             |
| Type of electric connection (EF003961)    | Other           |
| Diameter connection pin (EF006823)        | 1.4 mm          |
| Length pin (EF006825)                     | 2 mm            |
| Material insulation body (EF007543)       | Other           |

**CONTINUED****Technical Specifications**

| TECHNICAL ATTRIBUTE                                                      | VALUE            |
|--------------------------------------------------------------------------|------------------|
| Housing colour (EF000136)                                                | Black            |
| Inflammability class of insulation material according to UL94 (EF002521) | V0               |
| Operating temperature (EF002393)                                         | -40 °C           |
| Type of fastening (EF002442)                                             | Engage (snap)    |
| Type of banding (EF007011)                                               | Carton (for SMD) |

**Classification & Catalog Path**

|              |                                        |
|--------------|----------------------------------------|
| eCl@ss 7.1   | 21043711                               |
| eCl@ss 8.0   | 21043711                               |
| eCl@ss 9.0   | 21043711                               |
| ETIM 5.0     | EC002246                               |
| ETIM 6.0     | EC002246                               |
| ETIM 7.0     | EC002246                               |
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

**Additional Product Information**

Printed circuit board base case, nominal section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 2, number of poles: 14, family of articles: DMC 1.5/..-G2F-LR-THR, pitch: 3.5 mm, mounting: THR welding/wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, locking: Lock and Release, clamping type: Lock & Release air clamping (thread), packaging type: Boxed Packaging

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / DMC 1,5/14-G2F-3,5-LR P20THR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.