

INDUSTRIAL COMPONENT DATA

DMC 1,5/16-G2F-3,5-LR P26THR 1668503 PHOENIX CONTACT

Printed circuit board base housing, nominal section: 1...

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMC 1,5/16-G2F-3,5-LR P26THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	DMC 1,5/16-G2F-3,5-LR P26THR
Catalog number	1668503
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-F73C7B19F9
Generated	2026-08-03

Product Overview

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 2, number of poles: 16, family of articles: DMC 1.5/..-G2F-LR-THR, pitch: 3.5 mm, mounting: THR welding/wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of welding pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, locking: Lock and Release, clamping type: Lock & Release air clamping (thread), packaging type: Boxed Packaging

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 2, number of poles: 16, article family: DMC 1.5/..-G2F-LR-THR, Pitch: 3.5 mm, Mounting: THR Welding/Wave Soldering, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 2.6 mm, Number of Solder Pins per Potential: 1, Plug-in System: COMBICON DFMC 1.5, Plug-in Face Orientation: Standard, Locking: Snap-in Lock, Fixing Type: Lock & Lock; Release air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1668503 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector
Contact type (EF001587)
Pin
Number of plug-in contact rows (EF006935)
2
Modular spacing contacts (EF007326)
3.5 mm
Modular spacing connections (EF006827)
3.5 mm
Rated current I_n (EF008250)
8 A
Rated voltage (EF000228)
160 V
Rated surge voltage (EF002993)
2.5 kV
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Material of contact surface (EF004020)
Tin
Type of electric connection (EF003961)
Other
Diameter connection pin (EF006823)
1.4 mm
Length pin (EF006825)
2.6 mm
Material insulation body (EF007543)
Other
Housing colour (EF000136)
Black
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-40 °C
Type of fastening (EF002442)
Engage (snap)
Type of banding (EF007011)
Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMC 1,5/16-G2F-3,5-LR P26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.