

INDUSTRIAL COMPONENT DATA

DMCV 1,5/10-G1F-3,5-LRP26AUTHR 1105607 PHOENIX CONTACT Printed circuit board base housing, nominal section: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMCV 1,5/10-G1F-3,5-LRP26AUTHR



Manufacturer	PHOENIX CONTACT
MPN / Reference	DMCV 1,5/10-G1F-3,5-LRP26AUTHR
Catalog number	1105607
Category	Printed circuit board connector
Minimum order	1000 Pcs
Document ID	EO-33B39FA70C
Generated	2026-08-03

Product Overview

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Au, contact connection type: Male, number of potentials: 20, number of rows: 2, number of poles: 10, number of connections: 20, article family: DMCV 1.5/..-G1F-THR, pitch: 3.5 mm, mounting: THR welding/wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Lock & Release air clamping (thread), packaging type: boxed

PCB headers, nominal cross section: 1.5 mm², color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Gold, contact connection type: Pin, number of potentials: 20, number of rows: 2, number of positions: 10, number of connections: 20, product range: DMCV 1,5/..-G1F-THR, pitch: 3.5 mm, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1,5, Pin connector pattern alignment: Standard, locking: Snap-in locking, mounting: Lock & release threaded flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Connectors S
Product type PCB headers

Product family DMCV 1,5/..-G1F-THR

Number of positions 10

Pitch 3.5 mm

Number of connections 20

Number of rows 2

Number of potentials 20

Pin layout Linear pinning

Solder pins per potential 1

Electrical propertiesNominal current IN 8 A

Nominal voltage UN 160 V

Degree of pollution 3

Rated voltage (III/3) 160 V

Rated surge voltage (III/3) 2.5 kV

Rated voltage (III/2) 160 V

Rated surge voltage (III/2) 2.5 kV

Rated voltage (II/2) 250 V

Rated surge voltage (II/2) 2.5 kV

MountingMounting type THR soldering

Pin layout Linear pinning

Flange

Tightening torque 0.2 Nm

Processing notes

Process Reflow/wave soldering

Moisture Sensitive Level MSL 1

Classification temperature Tc 260 °C

Solder cycles in the reflow 3

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics partially gold-plated

Metal surface contact area (top layer) Gold (0.8 - 1.4 µm Au)

Metal surface contact area (middle layer) Nickel (2 - 4 µm Ni)

Metal surface soldering area (top layer) Tin (3 - 5 µm Sn)

Metal surface soldering area (middle layer) Nickel (2 - 4 µm Ni)

Material data - housing

Color (Housing) black (9005)

Insulating material LCP

Insulating material group IIIa

CTI according to IEC 60112 175

Flammability rating according to UL 94 V0

DimensionsDimensional drawing

Pitch 3.5 mm

Width [w] 42 mm

Heigh...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMCV 1,5/10-G1F-3,5-LRP26AUTHR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.