

INDUSTRIAL COMPONENT DATA

DMCV 1,5/17-G1F-3,5-LR P26THR 1874991 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMCV 1,5/17-G1F-3,5-LR P26THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	DMCV 1,5/17-G1F-3,5-LR P26THR
Catalog number	1874991
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-4B86F14D84
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 34, number of rows: 2, number of poles: 17, number of connections: 34, family of articles: DMCV 1.5/.. -G1F-THR, pitch: 3.5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, lock: Snap-in lock, fixing type: Lock & Release air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1874991

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626339702

Weight per Piece (excluding packing) 6.960 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 10.6 mm

Width 66.5 mm

Pitch 3.5 mm

Dimension a 56 mm

Width [w] 66.5 mm

Height [h] 12 mm

Height 10 mm

Length of the solder pin 2.6 mm

Pin dimensions 0.8 x 0.8 mm

Pin spacing 5.50 mm

Length 10.6 mm

General

Range of articles DMCV 1,5/..-G1F-THR

Insulating material group IIIa

Rated voltage (III/2) 160 V

Nominal current IN 8 A

Flammability rating according to UL 94 V0

Color black

Number of positions 17

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

ClassificationseCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1874991 Connectors (EC002637)

Feature Name**Feature Value**

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

34

Number of plug-in contact rows (EF006935)

2

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMCV 1,5/17-G1F-3,5-LR P26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.