

INDUSTRIAL COMPONENT DATA

DMCV 1,5/ 4-G1F-3,5-LR P35 1053974 PHOENIX CONTACT

Housing base for printed circuit board, nominal current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMCV 1,5/ 4-G1F-3,5-LR P35



Manufacturer	PHOENIX CONTACT
MPN / Reference	DMCV 1,5/ 4-G1F-3,5-LR P35
Catalog number	1053974
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-B0752B5908
Generated	2026-08-05

Product Overview

Housing base for printed circuit board, nominal current: 8 A, voltage and sizing (III/2): 160 V, number of poles: 4, pitch: 3.5 mm, color: green, surface of contact: Tin, assembly: wave Soldering

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 2, number of poles: 4, number of connections: 8, article family: DMCV 1.5/.. -G1F, pitch: 3.5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, lock: Snap-in lock, fixing type: Lock & Release air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1053974 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

8

Number of plug-in contact rows (EF006935)

2

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rated current I_n (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

3.5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of fastening (EF002442)

Engage (snap)

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMCV 1,5/ 4-G1F-3,5-LR P35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.