

**INDUSTRIAL COMPONENT DATA**

# DMCV 1,5/ 6-G1-3,5 P26THR R44 1341991 PHOENIX CONTACT

## Printed circuit board base housing, nominal section: 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMCV 1,5/ 6-G1-3,5 P26THR R44



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | DMCV 1,5/ 6-G1-3,5 P26THR R44   |
| Catalog number  | 1341991                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1100 Pcs                        |
| Document ID     | EO-9B39E7471D                   |
| Generated       | 2026-08-05                      |

### Product Overview

Printed circuit board base housing, nominal section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 2, number of poles: 6, family of articles: DMCV 1.5/..-G1-THR, pitch: 3.5 mm, mounting: THR welding/wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, locking: without, clamping type: without, packaging type: 44 mm wide strap

Connector for printed circuit board, nominal section: 1.5 mm<sup>2</sup>, colour: black, rated current: 8 A, dimensioning voltage (III/2): 160 V, surface contacts: Tin, contact type: Male, Number of rows: 2, Number of poles per row: 6, article family: DMCV 1.5/..-G1-THR, pitch: 3.5 mm, mounting: SOLDER THR, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, plug-in system: MINI COMBICON - DFMC 1.5, Plug-in face orientation: Standard, Locking: sin, fixing type: sin, packaging type: boxed packaging

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

### Additional Product Information

ETIM for 1341991 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin  
Number of plug-in contact rows (EF006935)  
2  
Modular spacing contacts (EF007326)  
3.5 mm  
Modular spacing connections (EF006827)  
3.5 mm  
Rated current  $I_n$  (EF008250)  
8 A  
Rated voltage (EF000228)  
160 V  
Rated surge voltage (EF002993)  
2.5 kV  
Over voltage category (EF006785)  
III  
Pollution degree (EF006786)  
2  
Material of contact surface (EF004020)  
Tin  
Type of electric connection (EF003961)  
Other  
Diameter connection pin (EF006823)  
1.4 mm  
Length pin (EF006825)  
2 mm  
Material insulation body (EF007543)  
Other  
Housing colour (EF000136)  
Black  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Operating temperature (EF002393)  
-40 °C  
Type of fastening (EF002442)  
Other  
Type of banding (EF007011)  
Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMCV 1,5/ 6-G1-3,5 P26THR R44 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.