

INDUSTRIAL COMPONENT DATA

PTTBS 2,5-TWIN/2P 3210604 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTBS 2,5-TWIN/2P



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTBS 2,5-TWIN/2P
Catalog number	3210604
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-C61115BD19
Generated	2026-08-04

Product Overview

Double-level terminal block

Double-deck terminal block, The maximum load current must not be exceeded by the sum current of all connected conductors. The current and voltage are determined by the connector used., nominal voltage: 500 V, nominal current: 18 A, connection type: Push-in connection / plug-in connection, 1st and 2nd floor, Dimensioning section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3210604

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 288 (C-1-2017)

GTIN 4055626004402

Weight per Piece (excluding packing) 16.750 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 6
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 18 A (observe derating)
Maximum load current 18 A (with 4 mm² conductor cross section)
Nominal voltage U_N 500 V
Open side panel Yes
Insertion/withdrawal cycles mechanical 100
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of tight fit on support Test passed
Setpoint 1 N
Short circuit stability result Test passed
Conductor cross section short circuit testing 2.5 mm²
Short-time current 0.3 kA
Result of thermal test Test passed
Proof of thermal characteristics (needle flame) effective duration 30 s
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, bo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTBS 2,5-TWIN/2P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.