

INDUSTRIAL COMPONENT DATA

PTTBS 2,5 3209604 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTBS 2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTBS 2,5
Catalog number	3209604
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-4620D6A4C4
Generated	2026-08-03

Product Overview

Double-level terminal block

Double-deck terminal block, nominal voltage: 500 V, nominal current: 22 A, connection type: Push-in connection, 1st and 2nd floor, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

Double-deck terminal, rated voltage: 500 V, rated current: 22 A, connection type: Push-in connection, 1. and 2. table, Dimensioning section: 2.5 mm², Section: 0.14 mm² - 4 mm², Mounting type: NS 35/7.5, NS 35/15, Colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3209604

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 83 (C-1-2017)

GTIN 4046356330084

Weight per Piece (excluding packing) 11.610 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 2

Number of connections 4
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 22 A
Maximum load current 24 A (with 4 mm² conductor cross section)
Nominal voltage U_N 500 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Checking the mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
2.5 mm² / 0.7 kg
4 mm² / 0.9 kg
Tensile test result Test passed
Conductor cross section tensile test 0.14 mm²
Tractive force setpoint 10 N
Conductor cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTBS 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.