


INDUSTRIAL COMPONENT DATA

STTB 2,5/4P 3061486 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STTB 2,5/4P



Manufacturer	PHOENIX CONTACT
MPN / Reference	STTB 2,5/4P
Catalog number	3061486
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-37DCA819F4
Generated	2026-08-03

Product Overview

Double-level terminal block

Double-level terminal, Current and voltage are determined by the connector used., nominal voltage: 500 V, nominal current: 22 A, connection type: Plug-in connection, 1. And 2nd floor, connection on the left, Dimensioning section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², mounting class: NS 35/15, NS 35/7.5, color: gray

Double-level terminal block, Current and voltage are determined by the plug used., nom. voltage: 500 V, nominal current: 22 A, connection method: Plug-in connection, 1st and 2nd level connection left, Rated cross section: 2.5 mm², cross section: 0.08 mm² - 4 mm², mounting type: NS 35/15, NS 35/7.5, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Technical dataNotesGeneral Current and voltage are determined by the plug used.

Product propertiesProduct type Plug-in terminal block

Product family STTB

Area of application Railway industry

Machine building

Plant engineering

Number of connections 4

Number of rows 2

Potentials 2

Data management status
Article revision 02
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical properties Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.77 W
Connection data Number of connections per level 2
Nominal cross section 2.5 mm²
1st and 2nd level connection left
Connection in acc. with standard IEC 61984
Conductor cross section rigid 0.08 mm² ... 4 mm²
Cross section AWG 28 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.08 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 28 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm²
Nominal current 22 A
Maximum load current 22 A
Nominal voltage 500 V
Nominal cross section 2.5 mm²
Dimensions Width 5.2 mm
End cover width 2.2 mm
Height 98.8 mm
Depth on NS 35/7,5 47.5 mm
Depth on NS 35/15 55 mm
Material specifications Color gray (RAL 7042)
Flammability rating according to UL 94 V0
Insulating material group I
Insulating material P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STTB 2,5/4P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.