

INDUSTRIAL COMPONENT DATA

DP-LPO 4 3270523 PHOENIX CONTACT Spacer plate, depth: 24.4 mm, width: 6.2 mm, height: 18.5 mm, number of pol..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-LPO 4



Manufacturer	PHOENIX CONTACT
MPN / Reference	DP-LPO 4
Catalog number	3270523
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-61AFE6A687
Generated	2026-08-04

Product Overview

Spacer plate, depth: 24.4 mm, width: 6.2 mm, height: 18.5 mm, number of poles: 1, color: gray

Spacer partition, length: 18.5 mm, width: 6.2 mm, height: 24.4 mm, number of poles: 1, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Partition plate

Number of positions 1

Ambient conditionsAmbient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C ()

Permissible humidity (storage/transport) 30 % ... 70 %

Material specificationsColor gray

Material PA

Flammability rating according to UL 94 V0

Static insulating material application in cold -60 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
DimensionsWidth 6.2 mm
Height 18.5 mm
Depth 24.4 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C ()
Permissible humidity (storage/transport) 30 % ... 70 %
ETIM for 3270523 Terminal blocks (EC000886)
Feature Name
Feature Value
Colour (EF000007)
Grey
Thickness (EF000125)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-LPO 4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.