

INDUSTRIAL COMPONENT DATA

DP-MUTTB 2,5 1462738 PHOENIX CONTACT Partition spacer, depth: 24.1 mm, width: 2.6 mm, height: 62.8 mm, colour..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-MUTTB 2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	DP-MUTTB 2,5
Catalog number	1462738
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-988D22F4E3
Generated	2026-08-05

Product Overview

Partition spacer, depth: 24.1 mm, width: 2.6 mm, height: 62.8 mm, colour: grey

Spacer partition, length: 62.8 mm, width: 2.6 mm, height: 24.1 mm, colour: grey

Spacer plate, depth: 24.1 mm, width: 2.6 mm, height: 62.8 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Partition plate

Insulation characteristics

Overvoltage category III

Ambient conditionsAmbient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

Material specificationsColor gray

Material PA

Flammability rating according to UL 94 V0

Insulating material group I

Insulating material PA

DimensionsWidth 2.6 mm

Height 62.8 mm

Depth 24.1 mm

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

ETIM for 1462738 Terminal blocks (EC000886)

Feature Name

Feature Value

Colour (EF000007)

Grey

Thickness (EF000125)

2.575 mm

Inflammability class of insulation material according to UL94 (EF002521)

V0

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-MUTTB 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.