

INDUSTRIAL COMPONENT DATA

DP-RSCWE 6-3 3069314 PHOENIX CONTACT Spacer plate

Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-RSCWE 6-3



Manufacturer	PHOENIX CONTACT
MPN / Reference	DP-RSCWE 6-3
Catalog number	3069314
Category	Endplate and partition plate for terminal block
Minimum order	1 Pcs
Document ID	EO-150C3C5B9E
Generated	2026-08-05

Product Overview

Spacer plate

Spacer partition, length: 80.9 mm, width: 8.2 mm, height: 70.8 mm, number of poles: 1, colour: grey

Spacer plate, depth: 70.8 mm, width: 8.2 mm, height: 80.9 mm, number of poles: 1, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3069314

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 619 (C-1-2017)

GTIN 4055626157573

Weight per Piece (excluding packing) 14.100 g

Custom tariff number 85389099

Country of origin PL (Poland)

General

Number of positions 1

Color gray

Material PA

Flammability rating according to UL 94 V0

Overvoltage category III

Insulating material group I

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Dimensions

Width 8.2 mm

Length 80.9 mm

Height 70.8 mm

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-RSCWE 6-3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.