

INDUSTRIAL COMPONENT DATA

FBP-2/12 3069883 PHOENIX CONTACT Dummy plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBP-2/12



Manufacturer	PHOENIX CONTACT
MPN / Reference	FBP-2/12
Catalog number	3069883
Category	Installation clamp for meters
Minimum order	1 Pcs
Document ID	EO-CBF4CD6F9B
Generated	2026-08-05

Product Overview

Dummy plug

Blind plug, pitch: 8.2 mm, length: 72.9 mm, width: 130.8 mm, number of poles: 12, color: gray, mounting class: Insert in base strip

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3069883

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 604 (C-1-2017)

GTIN 4046356962452

Weight per Piece (excluding packing) 126.500 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 12

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Overvoltage category III

Insulating material group I

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Dimensions

Width 130.8 mm

Length 72.9 mm

Pitch 8.2 mm

Mounting

Mounting type Insertion in base strip

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for r...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBP-2/12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.