

**INDUSTRIAL COMPONENT DATA**

# E PE A 75X80X75 0899338 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: E PE A 75X80X75



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | PHOENIX CONTACT                      |
| MPN / Reference | E PE A 75X80X75                      |
| Catalog number  | 0899338                              |
| Category        | Enclosure/switchgear cabinet (empty) |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-5CCDA35BE6                        |
| Generated       | 2026-08-05                           |

## Product Overview

Junction box

Empty housing, material: Fiberglass-reinforced polyester, squirrel gray RAL 7000, 75 mm x 80 mm x 75 mm, lock type: Screw-on lid

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                           |
|--------------|-------------------------------------------|
| Catalog path | PHOENIX CONTACT > Enclosures connectivity |
|--------------|-------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0899338

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 546 (C-3-2017)

GTIN 4055626276076

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 85389099

Country of origin IN (India)

General

Type Empty enclosure with cover

Note Prepared for direct installation of a DIN rail

Color squirrel gray RAL 7000

Flammability rating according to UL 94 V0

Direct DIN rail mounting yes

Useable DIN rail type NS 15

Dimensions

Width 75 mm

Height 80 mm

Depth 75 mm

Clearance width, maximum DIN rail length 63 mm

Assembly length, max. 49 mm

General

Housing material Polyester fiberglass reinforced

Cover fastening Screw-on cover

Note Plus/minus screw

Fixing device Integrated blind hole

External fixing clips available as an option

Seal material Chloroprene

Components halogen-free

Ambient conditions

Degree of protection of housing (IP) IP66

Protection class II

Degree of protection (IK) 7.00 J EN 60079-0

Temperature in operating conditions -40 °C ... 100 °C

Standards and Regulations

Standards/regulations EN 60079-0

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 10.0.127180190eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027141137eCl@ss 5.127180100eCl@ss  
6.027180100eCl@ss 7.027180190eCl@ss 8.027180190eCl@ss 9.027180190

ETIM 3.0EC000897ETIM 4.0EC000761ETIM 5.0EC000261ETIM 6.0E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E PE A 75X80X75 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.