

**INDUSTRIAL COMPONENT DATA**

# E PX A 75X80X56 0899300 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: E PX A 75X80X56



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | PHOENIX CONTACT                      |
| MPN / Reference | E PX A 75X80X56                      |
| Catalog number  | 0899300                              |
| Category        | Enclosure/switchgear cabinet (empty) |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-C0D7132D0E                        |
| Generated       | 2026-08-04                           |

## Product Overview

Junction box

Empty housing, material: Fiberglass-reinforced polyester, with graphite supplement, black, 75 mm x 80 mm x 56 mm, type of closure: Screw-on lid

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Enclosures connectivity

## Additional Product Information

Key Commercial Data

Orderkey 0899300

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 536 (C-3-2017)

GTIN 4055626275598

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 85389099

Country of origin IN (India)

General

Type Ex empty enclosure with cover

Note Prepared for direct installation of a DIN rail

Color black

Flammability rating according to UL 94 V0

Direct DIN rail mounting yes

Useable DIN rail type NS 15

Dimensions

Width 75 mm

Height 80 mm

Depth 56 mm

Clearance width, maximum DIN rail length 63 mm

Assembly length, max. 49 mm

General

Housing material Glass-fiber-reinforced polyester with added graphite

Cover fastening Screw-on cover

Note Plus/minus screw

Fixing device External fixing clips available as an option

Integrated blind hole

Seal material Silicon

Components halogen-free

Ambient conditions

Degree of protection of housing (IP) IP66

Protection class II

Degree of protection (IK) 7.00 J EN 60079-0

Temperature in operating conditions -55 °C ... 127 °C

Standards and Regulations

Standards/regulations EN 60079-0

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 10.0.127180190eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027141137eCl@ss 5.127180100eCl@ss  
6.027180100eCl@ss 7.027180190eCl@ss 8.027180190eCl@ss 9.027180190

ETIM 3.0EC000897ETIM 4.0EC000761ETIM 5.0EC000261ETIM 6....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E PX A 75X80X56 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.