

**INDUSTRIAL COMPONENT DATA**

# E-WML 14 (25X19)R YE 1199681 PHOENIX CONTACT Cable wrapping label, Roll, yellow, unlabelled, labelable with:...

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WML 14 (25X19)R YE



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | PHOENIX CONTACT      |
| MPN / Reference | E-WML 14 (25X19)R YE |
| Catalog number  | 1199681              |
| Category        | Cable coding system  |
| Minimum order   | 1 Pcs                |
| Document ID     | EO-8EAFB6E1A4        |
| Generated       | 2026-08-05           |

## Product Overview

Cable wrapping label, Roll, yellow, unlabelled, labelable with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting class: glued, cable diameter range: 6.1 ... 14.2 mm, usable area: 25.4 x 19.1 mm, number of individual indexes: 2450

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Technical dataItem PropertiesProduct Type Unlabeled conductor marker

Execution Label

Signage

Number of Individual Indexes 2450

Number of individual labels per line 1

Marking technology Thermal Transfer for Rolls

Connection dataAWG Conductor Section (Converted according to IEC)

DimensionsWidth 25.4 mm

Longitude 63.5 mm

Material DataRoHS Compliant Yes

Adhesive Acrylate

Colour yellow

Material PVC

Substances contained Silicone-free  
Cable/LineCable Outer Diameter 14.2 mm  
6.1 mm ... 14.2 mm  
Environmental and life-life conditionsScratch test to determine scratch resistance  
Test Specification DIN EN ISO 1518-1:2019-10 (in accordance with the law)  
Demand  $\geq 5$  N  
Result Approved Test  
tesafilm tape test  
Test Specification DIN EN ISO 2409:2013 (conforming)  
Result Approved Test  
Resistance to ultraviolet rays  
Test Specification DIN EN ISO 4892-2:2013-06 (conformity)  
Result Approved Test  
Duration of the trial 96 h  
Procedure Artificial radiation with xenon arc lamp  
Temperature-controlled storage  
Test Specification IEC 60068-2-2:2007-07  
Result Approved Test  
Duration 96 h  
Test Temperature 100 °C  
Temperature resistance  
Test Specification ANSI/UL 969-2018:03 (Compliant)  
Duration of the trial 240 h  
Rating 100 °C (121 °C) Approved Test  
Resistance to chemicals, oils and fuels  
Test Specification ISO 175:2010 (Conformity)  
Duration of the trial 168 h  
Sodium hydroxide 0.1 mol/l  
[CAS No. 1310-73-2] Approved Test  
Salt water (350 g/l)  
[CAS No. - ] Approved Test  
Diesel  
[CAS No. 68476-34-6] Approved Test  
MRI...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WML 14 (25X19)R YE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.