

**INDUSTRIAL COMPONENT DATA**

# E-WML 5 (25X10)R YE 1199661 PHOENIX CONTACT Cable wrapping label, Roll, yellow, unlabelled, labelable with: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WML 5 (25X10)R YE



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | E-WML 5 (25X10)R YE |
| Catalog number  | 1199661             |
| Category        | Cable coding system |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-CB8B0AA82E       |
| Generated       | 2026-08-03          |

## Product Overview

Cable wrapping label, Roll, yellow, unlabelled, labelable with: THERMOMARK E.WRAP, cable diameter range: 3.2 ... 5.1 mm, mounting type: glued, Number of individual indexes: 5800, text field height: 9.5 mm, text field width: 25.4 mm

Cable Wrap Label, Roll, Yellow, Unlabeled, Labelable with: THERMOMARK E.WRAP, THERMOMARKE.300 (D)/600 (D), Mounting Class: Glued, Cable Diameter Range: 3.2 ... 5.1 mm, usable area: 25.4x9.5mm, Number of individual indexes: 5800

Wire-wrap label, Roll, yellow, unlabeled, can be labeled with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting type: adhesive, cable diameter range: 3.2 ... 5.1 mm, lettering field size: 25.4 x 9.5 mm, Number of individual labels: 5800

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Label

Marking

Number of individual labels 5800

Number of individual labels per row 1

Identification technology Thermal transfer for rolls

Connection dataCross section AWG (converted acc. to IEC)

DimensionsWidth 25.4 mm

Length 25.4 mm  
Material specifications RoHS compliant yes  
Adhesive Acrylic  
Color yellow  
Material PVC  
Components Silicone-free  
Cable/line External cable diameter 5.1 mm  
3.2 mm ... 5.1 mm  
Environmental and real-life conditions Scratch test for the determining scratch resistance  
Specification DIN EN ISO 1518-1:2019-10 (following)  
Requirements  $\geq 5$  N  
Result Test passed  
Tesa film test  
Specification DIN EN ISO 2409:2013 (following)  
Result Test passed  
UV resistance  
Specification ISO 4892-2:2013-03 (following)  
Result Test passed  
Test duration 96 h  
Specification IEC 60068-2-2:2007-07  
Result Test passed  
Duration 96 h  
Temperature for testing 100 °C  
Temperature resistance  
Specification ANSI/UL 969-2018:03 (following)  
Test duration 240 h  
Rating 100 °C (121 °C) Test passed  
Specification ISO 175:2010 (following)  
Test duration 168 h  
Diesel  
[CAS No. 68476-34-6] Test passed  
IRM 901 Test passed  
IRM 902 Test passed  
Testing in a condensation changing climate in the presence of sulfur dioxide  
Specification DIN 50018:2013-05  
Result Test passed  
Climate level AHT 1.0 S  
Cycles 2  
Salt spray test  
Specification DIN EN 60068-2-11:2000-02  
Result Test passed  
Test duration 96 h  
Ambient conditions  
Ambient temperature (operation) -4...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WML 5 (25X10)R YE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.