

INDUSTRIAL COMPONENT DATA

E-WML 6 (25X13)R 1343122 PHOENIX CONTACT Cable wrapping label, Roll, white, unlabelled, labelable with: THER..

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WML 6 (25X13)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	E-WML 6 (25X13)R
Catalog number	1343122
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-1CE7AF2F71
Generated	2026-08-03

Product Overview

Cable wrapping label, Roll, white, unlabelled, labelable with: THERMOMARK E.WRAP, cable diameter range: 4 ... 6 mm, mounting type: glued, Number of individual indexes: 4750, text field height: 12.7 mm, text field width: 25.4 mm

Cable Wrap Label, Roll, White, Unlabeled, Labelable with: THERMOMARK E.WRAP, THERMOMARKE.300 (D)/600 (D), Mounting Class: Glued, Cable Diameter Range: 4 ... 6 mm, usable area: 25.4x12.7mm, Number of individual indexes: 4750

Wire-wrap label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting type: adhesive, cable diameter range: 4 ... 6 mm, lettering field size: 25.4 x 12.7 mm, Number of individual labels: 4750

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Label

Marking

Number of individual labels 4750

Number of individual labels per row 1

Identification technology Thermal transfer for rolls

Connection dataCross section AWG (converted acc. to IEC)

DimensionsWidth 25.4 mm

Length 31.8 mm

Material specificationsRoHS compliant yes

Adhesive Acrylic

Color white

Material PVC

Components Silicone-free

Cable/lineExternal cable diameter 6.1 mm

4 mm ... 6 mm

Environmental and real-life conditionsScratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Specification IEC 60068-2-2:2007-07

Result Test passed

Duration 96 h

Temperature for testing 100 °C

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 100 °C (121 °C) Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Diesel

[CAS No. 68476-34-6] Test passed

IRM 901 Test passed

IRM 902 Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification DIN 50018:2013-05

Result Test passed

Climate level AHT 1.0 S

Cycles 2

Salt spray test

Specification DIN EN 60068-2-11:2000-02

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -40 °C....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WML 6 (25X13)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.