

INDUSTRIAL COMPONENT DATA

E-WMS 9,5 (EX16)R 1221590 PHOENIX CONTACT Heat-shrink sleeve, Roll, white, unlabeled, labelable with: THERMO..

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WMS 9,5 (EX16)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	E-WMS 9,5 (EX16)R
Catalog number	1221590
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-3A54746267
Generated	2026-08-05

Product Overview

Heat-shrink sleeve, Roll, white, unlabeled, labelable with: THERMOMARK E.SLEEVE, cable diameter range: 3.2 ... 9.5 mm, mounting class: sliding, cable diameter range (automated processing): 3.2 ... 8.5 mm, Number of individual indexes: 1, length. Roll: 20 m, text field height: 16 mm
Heat shrink tubing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

ETIM for 1221590 Cable terminations and insulation products (EC001530)

Feature Name

Feature Value

Model (EF000010)

Roller shape

Type (EF001139)

Medium-walled

Tooththing (EF009649)

None

Material (EF002169)

Other

Core diameter (EF005497)

3.2 mm

Cable diameter (EF002356)

3.2 mm

Width (EF000008)

16 mm

Colour (EF000007)

White

Fluorescent (EF009518)

No

With label space (EF003456)

Yes

Mounting method (EF000003)

Suspend

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WMS 9,5 (EX16)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.