

INDUSTRIAL COMPONENT DATA

EC 25 TR 3240185 PHOENIX CONTACT Europe connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: EC 25 TR



Manufacturer	PHOENIX CONTACT
MPN / Reference	EC 25 TR
Catalog number	3240185
Category	Single- and multi-pole terminal strip
Minimum order	10 Pcs
Document ID	EO-D9C8FF5CE6
Generated	2026-08-05

Product Overview

Europe connectors

Europa terminal block made of polyamide, transparent, for connecting rigid and flexible conductors with and without ferrules with a cross-section of 10 to 25 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 3240185

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 603 (C-3-2017)

GTIN 4046356457897

Weight per Piece (excluding packing) 117.440 g

Custom tariff number 85369010

Country of origin AT (Austria)

General

Number of positions 12

Number of levels 1

Number of connections 24

Nominal cross section 25 mm²
Color transparent
Insulating material PA
Flammability rating according to UL 94 V2
Ambient temperature (operation) -40 °C ... 110 °C
Maximum load current 101 A (with 25 mm² conductor cross section)
Nominal current I_N 101 A (with 25 mm² conductor cross section)
Nominal voltage U_N 750 V
Open side panel No
Dimensions
Width 30 mm
Length 187.3 mm
Height 28 mm
Depth 30 mm
Drill hole spacing 16 mm
Pitch 16 mm
Connection data
Connection method Screw connection
Conductor cross section solid min. 10 mm²
Conductor cross section solid max. 25 mm²
Conductor cross section AWG min. 8
Conductor cross section AWG max. 4
Conductor cross section flexible min. 10 mm²
Conductor cross section flexible max. 25 mm²
Min. AWG conductor cross section, flexible 8
Max. AWG conductor cross section, flexible 4
Conductor cross section flexible, with ferrule without plastic sleeve min. 4 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²
2 c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EC 25 TR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.