

INDUSTRIAL COMPONENT DATA

ECS-B-122X109-L-UV-V GY 1054702 PHOENIX CONTACT

Snap-in locking vented enclosure of the ECS Family. IP66/67/..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-B-122X109-L-UV-V GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-B-122X109-L-UV-V GY
Catalog number	1054702
Category	Extruded profile modular housing
Minimum order	5 Pcs
Document ID	EO-97E3F07019
Generated	2026-08-06

Product Overview

Snap-in locking vented enclosure of the ECS Family. IP66/67/69 rated when mated with associated faceplate. Color: Grey (7042), Width: 172 mm, Height: 116 mm, Depth: 64 mm

Ventilated housing from the ECS family, locking by snapping. IP66/67/69 protection rating in case of combination with the corresponding faceplate. Colour: grey (7042), width: 172 mm, height: 116 mm, depth: 64 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 1054702

Packing unit 1 pc

GTIN 4055626690919

Weight per Piece (excluding packing) 9.600 g

Custom tariff number 85389099

Country of origin US (United States)

Drawings

Measurements

Ambient conditions

Packaging information

Environmental Product Compliance

Item properties

Material specifications

PCB data

Standards and regulations

Classifications

Drawings

Dimensional drawing

[Back to top](#)Item properties

Type ECS-B-122X109-L-UV-V GY

Order No. 1054702

Type Snap-in locking

Mounting type Wall or panel mount. Pole mount with accessory.

Ventilation integrated pressure compensation membrane

[Back to top](#)Measurements

Dimensional drawing

Width [w] 172 mm

Height [h] 116 mm

Depth [d] 64 mm

[Back to top](#)Material specifications

Color (RAL) gray (7042)

Flammability rating according to UL 94 V0

Housing material PC (polycarbonate)

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

[Back to top](#)PCB data

PCB thickness 1.57 mm ... 2.36 mm

[Back to top](#)Packaging information

Pieces per package 5

Denomination packing units Pcs.

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27180401

eCl@ss 4.1 27180401

eCl@ss 5.0 27180505

eCl@ss 5.1 27180505

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 271827...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-B-122X109-L-UV-V GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.