

## INDUSTRIAL COMPONENT DATA

# ECS-KIT-64X80-S-UV-7042 1319373 PHOENIX CONTACT

## Empty box for wall or pole mounting, grey 7042, modular elec..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-KIT-64X80-S-UV-7042



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | PHOENIX CONTACT         |
| MPN / Reference | ECS-KIT-64X80-S-UV-7042 |
| Catalog number  | 1319373                 |
| Category        | Electronic enclosure    |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-D2D53A513B           |
| Generated       | 2026-08-02              |

### Product Overview

Empty box for wall or pole mounting, grey 7042, modular electronics enclosure with faceplate, for outdoor applications, degree of protection: IP66/67/69, width 97 mm, height 87 mm, depth 42 mm, printed circuit board surface 4100 mm<sup>2</sup>

Empty enclosure for wall or mast mounting, gray (7042), modular electronics housing with front plate, for outdoor applications, degree of protection: IP66/IP67/IP69, width: 97 mm, height: 87 mm, depth: 42 mm, PCB surface: 4100 mm<sup>2</sup>

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.

Product propertiesProduct type Stackable housing set

Type Screw locking mechanism

Housing type outdoor housings

Housing series ECS

DimensionsDimensional drawing

Width 97.8 mm

Height 89.4 mm

Depth 45.1 mm

Material specificationsColor gray (7042)

Flammability rating according to UL 94 V0  
Housing material PC (polycarbonate)  
Environmental and real-life conditions Ambient conditions  
Max. NEMA code to attain 6  
Ambient temperature (operation) -40 °C ... 100 °C  
Ambient temperature (storage/transport) -40 °C ... 100 °C  
PCB data Type of PCB mount Bolt mounting  
Total PCB surface 4100 mm<sup>2</sup>  
Mounting Mounting type Wall or panel mount. Pole mount with accessory.  
Packaging specifications Type of packaging packed in cardboard  
Outer packaging type Carton  
ETIM for 1319373 Cabinets and enclosures (EC001031)  
Feature Name  
Feature Value  
Material (EF002169)  
Other  
Colour (EF000007)  
Grey

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-KIT-64X80-S-UV-7042 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.