

INDUSTRIAL COMPONENT DATA

ECS-P-122X169-L-UV-CG GY 1050383 PHOENIX CONTACT

Snap-in locking cable gland faceplate of the ECS Family. IP..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-P-122X169-L-UV-CG GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-P-122X169-L-UV-CG GY
Catalog number	1050383
Category	Extruded profile modular housing
Minimum order	5 Pcs
Document ID	EO-3A7647CDF2
Generated	2026-08-06

Product Overview

Snap-in locking cable gland faceplate of the ECS Family. IP66/67/69 rated when mated with associated enclosure. Color: Grey (7042), Width: 196 mm, Height: 34 mm, Depth: 62 mm

Faceplate of the ECS family with cable gland, locking by snapping. IP66/67/69 protection rating in case of combination with the corresponding housing. Colour: grey (7042), width: 196 mm, height: 34 mm, depth: 62 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1050383

Packing unit 1 pc

GTIN 4055626666143

Weight per Piece (excluding packing) 1.000 g

Custom tariff number 85389099

Country of origin US (United States)

Drawings

Measurements

Ambient conditions

Packaging information

Environmental Product Compliance

Item properties

Material specifications

PCB data

Standards and regulations

Classifications

Drawings

Dimensional drawing

[Back to top](#)Item properties

Type ECS-P-122X169-L-UV-CG GY

Order No. 1050383

Type Snap-in locking

Connection Cable gland M20 x 1.5 (6 ... 12 mm)

Mounting type Mechanical latch to base

[Back to top](#)Measurements

Dimensional drawing

Width [w] 196 mm

Height [h] 34 mm

Depth [d] 62 mm

[Back to top](#)Material specifications

Color (RAL) gray (7042)

Flammability rating according to UL 94 V0

Housing material PC (polycarbonate)

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

[Back to top](#)PCB data

Number of PCB holders 1

[Back to top](#)Packaging information

Pieces per package 5

Denomination packing units Pcs.

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27180401

eCl@ss 4.1 27180401

eCl@ss 5.0 27180505

eCl@ss 5.1 27180505

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-P-122X169-L-UV-CG GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.