

INDUSTRIAL COMPONENT DATA

ECS-P-122X169-S-UV-1M12 GY 1050381 PHOENIX CONTACT

Screw locking one female M12 faceplate of the ECS Family...

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-P-122X169-S-UV-1M12 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-P-122X169-S-UV-1M12 GY
Catalog number	1050381
Category	Extruded profile modular housing
Minimum order	5 Pcs
Document ID	EO-620B35B4C4
Generated	2026-08-06

Product Overview

Screw locking one female M12 faceplate of the ECS Family. IP66/67/69 rated when mated with associated enclosure.

Color: Grey (7042), Width: 163 mm, Height: 30 mm, Depth: 62 mm

ECS family faceplate, SPEEDCON M12 female connector (1 unit), screw lock. IP66/67/69 protection rating in combination with the corresponding box. Color: gray (7042); width: 163 mm; height: 30 mm; Depth: 62 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1050381

Packing unit 1 pc

GTIN 4055626666228

Weight per Piece (excluding packing) 120.000 g

Custom tariff number 85389099

Country of origin US (United States)

Drawings

Measurements

Ambient conditions

Packaging information

Environmental Product Compliance

Item properties

Material specifications

PCB data

Standards and regulations

Classifications

Drawings

Dimensional drawing

[Back to top](#)Item properties

Type ECS-P-122X169-S-UV-1M12 GY

Order No. 1050381

Type Screw locking

Connection 1x M12 nut

Mounting type Screw locking

[Back to top](#)Measurements

Dimensional drawing

Width [w] 163 mm

Height [h] 30 mm

Depth [d] 62 mm

[Back to top](#)Material specifications

Color (RAL) gray (7042)

Flammability rating according to UL 94 V0

Housing material PC (polycarbonate)

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

[Back to top](#)PCB data

Number of PCB holders 1

[Back to top](#)Packaging information

Pieces per package 5

Denomination packing units Pcs.

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27180401

eCl@ss 4.1 27180401

eCl@ss 5.0 27180505

eCl@ss 5.1 27180505

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-P-122X169-S-UV-1M12 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.