

INDUSTRIAL COMPONENT DATA

ECS-P-122X169-S-UV1-B S1808 1518548 PHOENIX CONTACT

ECS Family Faceplate

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-P-122X169-S-UV1-B S1808



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-P-122X169-S-UV1-B S1808
Catalog number	1518548
Category	Electronic enclosure
Minimum order	25 Pcs
Document ID	EO-0FC425F26C
Generated	2026-08-06

Product Overview

ECS Family Faceplate
 outdoor housings, Faceplate, width: 163 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataProduct propertiesProduct type Front plate
 Housing type outdoor housings
 Ventilation openings present no
 Housing series ECS
 DimensionsDimensional drawing
 Width 163 mm
 Height 30 mm
 Depth 62 mm
 PCB design
 PCB thickness 1.57 mm ... 2.36 mm
 Material specificationsColor black (9005)
 Flammability rating according to UL 94 V0
 Surface characteristics untreated
 Impact strength IK08

Housing material PC (polycarbonate)
Environmental and real-life conditions Vibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 2000 - 10 Hz
Sweep speed 1 octave/min
Acceleration 15g (61.6 Hz ... 2000 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Mechanical strength / tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Frequency 50
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Semi-sinusoidal
Acceleration 50g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Salt spray test
Specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Degree of protection (IP code)
Specification IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Ambient conditions
Max. NEMA code to attain 6
Impact strength IK08
Ambient temperature (operation) -40 °C ... 100 °C
Ambient temperature (storage/transport) -40 °C ... 100 °C
PCB data Number of PCB holders 1
Thickness of the PCB 1.57 mm ... 2.36 mm
Mounting Mounting...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-P-122X169-S-UV1-B S1808 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.