

**INDUSTRIAL COMPONENT DATA**

# EEM-MA370-R 2907980 PHOENIX CONTACT Multi-functional energy measuring device with integrated Modbus RTU/TCP ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EEM-MA370-R



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | PHOENIX CONTACT                    |
| MPN / Reference | EEM-MA370-R                        |
| Catalog number  | 2907980                            |
| Category        | Multifunction measuring instrument |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-E77892CAF6                      |
| Generated       | 2026-08-03                         |

## Product Overview

Multi-functional energy measuring device with integrated Modbus RTU/TCP interface for measuring electrical parameters in low-voltage installations up to 690 V.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

Key Commercial Data

Orderkey 2907980

Packing unit 1 pc

Catalog page Page 203 (C-5-2019)

GTIN 4055626260570

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 90303100

Country of origin DE (Germany)

Dimensions

Input data

General

Connection data 2

UL data

Environmental Product Compliance

Ambient conditions

Output data

Connection data

Connection data 3

Standards and Regulations

Classifications

Dimensions

Width 90 mm

Height 80 mm

Depth 64 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -10 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 70 °C

Maximum altitude ≤ 2000 m

Max. permissible relative humidity (operation) ≤ 95 % (non-condensing)

Degree of protection IP40 (Display)

IP20 (Housing)

[Back to top](#)Input data

Measuring principle True r.m.s. value measurement

Acquisition of harmonics up to 63rd harmonic

Measured value AC sine (50/60 Hz)

Input name Voltage measuring input V1, V2, V3

Input voltage range 35 V AC ... 690 V AC (Phase/Phase)

20 V AC ... 400 V AC (Phase/neutral conductor)

60 V AC ... 2000000 V AC (primary)

60 V AC ... 400 V AC (secondary)

Surge voltage capacity 760 V AC (Phase/Phase)

Precision 0.2 %

Input name Current measurement I1, I2, I3

Input current 1 A (secondary)

5 A (secondary)

Current measuring range 1 A ... 20000 A (primary)

Overload capacity 6 A (Imax)

Response threshold from measuring range nominal value 10 mA (1 A)

Precision 0.2 %

Current overload 50 A for 1 s

Precision 0.5 %

Active energy (IEC 62053-22) Class...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EEM-MA370-R with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.