


INDUSTRIAL COMPONENT DATA

MC 1,5/ 7-STF-3,81 BD:1-7Q 1701682 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 7-STF-3,81 BD:1-7Q



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 7-STF-3,81 BD:1-7Q
Catalog number	1701682
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-1D45031057
Generated	2026-08-03

Product Overview

Plug

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: MC 1.5/.. -STF, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping shape: L Longitudinal slot, driver/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, locking: Screw locking, fixing type: Overhead clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1701682

Packing unit 1

GTIN 4046356561952

Custom tariff number 85366990

Dimensions

Length [l] 16.1 mm

Width [w] 37.06 mm

Height [h] 11.1 mm

Pitch 3.81 mm

Dimension a 22.86 mm

General

Range of articles MC 1,5/...-STF

Number of positions 7

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²**Connection data**Conductor cross section solid min. 0.14 mm²Conductor cross section solid max. 1.5 mm²Conductor cross section flexible min. 0.14 mm²Conductor cross section flexible max. 1.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.08 mm²2 conductors with same cross section, solid max. 0.5 mm²2 conductors with same cross section, stranded min. 0.08 mm²2 conductors with same cross section, stranded max. 0.75 mm²2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.34 mm²

2 conductors with same cross...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 7-STF-3,81 BD:1-7Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.