

INDUSTRIAL COMPONENT DATA

EH 17,5 F-FP/ABS-PC BK9005 1074614 PHOENIX CONTACT DIN rail housing, Filler plug for unoccupied terminal poi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 17,5 F-FP/ABS-PC BK9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 17,5 F-FP/ABS-PC BK9005
Catalog number	1074614
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-761DDD262F
Generated	2026-08-06

Product Overview

DIN rail housing, Filler plug for unoccupied terminal points, with vents, width: 16.3 mm, height: 13.67 mm, depth: 33.39 mm, color: black (9005)

Rail box, Blank plug for non-equipped terminal points (flat design), with ventilation slits, width: 16.3 mm, height: 33.39 mm, depth: 13.67 mm, colour: black (9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
 Orderkey 1074614
 Packing unit 1
 GTIN 4055626775623
 Custom tariff number 85389099
 Item properties
 Material data
 General information
 Standards and regulations
 Dimensions
 Ambient conditions
 Packaging information

[Classifications](#)[Item properties](#)[Brief article description](#) Filler plugs[Type](#) EH 17,5 F-FP/ABS-PC BK9005[Order No.](#) 1074614[Housing type](#) DIN rail housing[Housing series](#) EH[Type](#) Filler plug for unoccupied terminal points[Mounting type](#) Latching with upper housing part[Ventilation openings present](#) yes[Back to top](#)[Dimensions](#)[Width \[w \]](#) 16.3 mm[Height \[h \]](#) 13.67 mm[Depth \[d \]](#) 33.39 mm[Back to top](#)[Material data](#)[Color \(RAL\)](#) black (9005)[Flammability rating according to UL 94](#) V0[Housing material](#) ABS-PC[Back to top](#)[Ambient conditions](#)[Ambient temperature \(storage/transport\)](#) -40 °C ... 70 °C[Ambient temperature \(assembly\)](#) -5 °C ... 80 °C[Ambient temperature \(operation\)](#) -40 °C ... 80 °C (depending on power dissipation)[Back to top](#)[General information](#)[Type of note](#) Assembly instruction:[Note](#) Refer to the data sheet for the range in the download area.[Back to top](#)[Packaging information](#)[Pieces per package](#) 10[Denomination packing units](#) Pcs.[Back to top](#)[Standards and regulations](#)[Flammability rating according to UL 94](#) V0[Back to top](#)[Classifications](#)[eCl@ss](#)[eCl@ss 5.0](#) 27180506[eCl@ss 5.1](#) 27180500[eCl@ss 6.0](#) 27180800[eCl@ss 7.0](#) 27182702[eCl@ss 8.0](#) 27182702[eCl@ss 9.0](#) 27182702[Back to top](#)[ETIM](#)[ETIM 4.0](#) EC001031[ETIM 5.0](#) EC001031[ETIM 6.0](#) EC001031[ETIM 7.0](#) EC001031[Back to top](#)[UNSPSC...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 17,5 F-FP/ABS-PC BK9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.