

INDUSTRIAL COMPONENT DATA

EH 17,5-FP/ABS-PC BK9005 1071147 PHOENIX CONTACT DIN rail housing, Filler plug for unoccupied terminal point..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 17,5-FP/ABS-PC BK9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 17,5-FP/ABS-PC BK9005
Catalog number	1071147
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-1BECF473BB
Generated	2026-08-04

Product Overview

DIN rail housing, Filler plug for unoccupied terminal points, width: 16.3 mm, height: 13.67 mm, depth: 19.65 mm, color: black (9005)

Rail box, Blank plug for unequipped terminal points (high design), width: 16.3 mm, height: 19.65 mm, depth: 13.67 mm, colour: black (9005)

DIN rail housing, Filler plug for unoccupied terminal points (tall design), width: 16.3 mm, height: 19.65 mm, depth: 13.67 mm, color: black (similar RAL 9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Filler plug

Housing type DIN rail housing

Housing series EH

Product family EH..ABS-PC..

Type Filler plug for unoccupied terminal points (tall design)

Ventilation openings present no

Data management status

Article revision 00

DimensionsDimensional drawing

Width 16.3 mm
Height 19.65 mm
Depth 13.67 mm
Material specificationsColor (Housing) black (RAL 9005)
Flammability rating according to UL 94 V0
Housing material ABS-PC
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 80 °C
Relative humidity (storage/transport) 95 %
PCB dataType of PCB mount Slot
MountingMounting type Latching with upper housing part
ETIM for 1071147 Low-voltage industrial controls and switchgear (EC002779)
Feature Name
Feature Value
Type of enclosure (EF003086)
Open
Housing connectable (EF003088)
No
Suitable for rail mounting (EF003972)
No
Wall mounting possible (EF003973)
No
With integrated PCB-mounting connection system (EF003087)
No
Material (EF002169)
Other
Surface finishing (EF006569)
Other
Colour (EF000007)
Black
RAL-number (EF000116)
9005

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 17,5-FP/ABS-PC BK9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.