

**INDUSTRIAL COMPONENT DATA**

# EH 22,5-C SS/ABS-PC GY7035 1075366 PHOENIX CONTACT DIN rail housing, Upper part, connection opening on one s..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 22,5-C SS/ABS-PC GY7035



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | EH 22,5-C SS/ABS-PC GY7035       |
| Catalog number  | 1075366                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-CDC8E34CE9                    |
| Generated       | 2026-08-04                       |

## Product Overview

DIN rail housing, Upper part, connection opening on one side, width: 22.6 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (7035)

Rail box, Top of housing, tall design, connection hole on one side, connection hole on one side, width: 22.6 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (7035)

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1075366

Packing unit 1

GTIN 4055626780306

Custom tariff number 85389099

Drawings

Dimensions

Ambient conditions

General information

Standards and regulations

Item properties

Material data

[PCB data](#)

[Packaging information](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to topItem properties](#)

[Brief article description](#) Upper part of housing

Type EH 22,5-C SS/ABS-PC GY7035

Order No. 1075366

Housing type DIN rail housing

Housing series EH

Type Upper part

Max. IP code to attain IP20

Mounting type Snap in

Ventilation openings present no

Max. number of positions 5 (pitch: 3.5 mm)

[Back to topDimensions](#)

[Dimensional drawing](#)

Width [ w ] 22.6 mm

Height [ h ] 75.26 mm

Depth [ d ] 36.95 mm

Depth from base support surface [d] 19.95 mm

[Back to topMaterial data](#)

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS-PC

[Back to topAmbient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 80 °C

Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)

[Back to topPCB data](#)

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

[Back to topGeneral information](#)

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

[Back to topPackaging information](#)

Pieces per package 10

Denomination packing units Pcs.

[Back to topStandards and regulations](#)

Flammability rating according to UL 94 V0

[Back to topCl...](#)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 22,5-C SS/ABS-PC GY7035 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.