

INDUSTRIAL COMPONENT DATA

EH 22,5 F-C SS/ABS GY7035 2200674 PHOENIX CONTACT

Upper part of housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 22,5 F-C SS/ABS GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 22,5 F-C SS/ABS GY7035
Catalog number	2200674
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-2A4CAF5F7A
Generated	2026-08-05

Product Overview

Upper part of housing

Rail box, Top of housing, flat design, connection hole on one side, connection hole on one side, width: 22.6 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (7035)

DIN rail housing, Upper housing part, flat design, connection opening on one side, connection opening on one side, width: 22.6 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (similar RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Upper housing part

Housing type DIN rail housing

Housing series EH

Product family EH..F..ABS..

Max. number of positions 4 (pitch: 5 mm/5.08 mm)

5 (pitch: 3.81 mm)

Type Upper housing part, flat design, connection opening on one side

Ventilation openings present yes

Data management status

Article revision 00

DimensionsDimensional drawing

Width 22.6 mm

Height 75.26 mm

Depth 36.95 mm

Depth from base support surface 19.95 mm

Material specificationsColor (Housing) light gray (RAL 7035)

Flammability rating according to UL 94 HB

Housing material ABS

Surface characteristics untreated

Environmental and real-life conditionsVibration test

Specification IEC 60068-2-6:2007-12

Frequency 10 - 150 - 10 Hz

Sweep speed 1 octave/min

Amplitude 0.15 mm (10 Hz ... 58.1 Hz)

Acceleration 2g (58.1 Hz ... 150 Hz)

Test duration per axis 2.5 h

Test directions X-, Y- and Z-axis

Glow-wire test

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Thermal stability / ball thrust test

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20 N

Mechanical strength / tumbling barrel

Specification IEC 60998-1:2002-12

Height of fall 50 cm

Frequency 10

Shocks

Specification IEC 60068-2-27:2008-02

Pulse shape Half-sine

Acceleration 15g

Shock duration 11 ms

Number of shocks per direction 3

Test directions X-, Y- and Z-axis (pos. and neg.)

Degree....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 22,5 F-C SS/ABS GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.