

INDUSTRIAL COMPONENT DATA

EH 22,5-FP/ABS-PC GY7035 1071139 PHOENIX CONTACT DIN rail housing, Filler plug for unoccupied terminal point..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 22,5-FP/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 22,5-FP/ABS-PC GY7035
Catalog number	1071139
Category	Extruded profile modular housing
Minimum order	50 Pcs
Document ID	EO-61430AA82A
Generated	2026-08-06

Product Overview

DIN rail housing, Filler plug for unoccupied terminal points, width: 21.35 mm, height: 13.67 mm, depth: 19.65 mm, color: light gray (7035)

Rail box, Blank plug for non-equipped terminal points (tall design), width: 21.35 mm, height: 19.65 mm, depth: 13.67 mm, colour: light grey (7035)

DIN rail housing, Filler plug for unoccupied terminal points (tall design), width: 21.35 mm, height: 19.65 mm, depth: 13.67 mm, color: light gray (similar RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Filler plug

Housing type DIN rail housing

Housing series EH

Product family EH..ABS-PC..

Type Filler plug for unoccupied terminal points (tall design)

Ventilation openings present no

Data management status

Article revision 00

DimensionsDimensional drawing

Width 21.35 mm
Height 19.65 mm
Depth 13.67 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
Housing material ABS-PC
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 80 °C
Relative humidity (storage/transport) 95 %
PCB dataType of PCB mount Slot
MountingMounting type Latching with upper housing part
ETIM for 1071139 Low-voltage industrial controls and switchgear (EC002779)
Feature Name
Feature Value
Type of enclosure (EF003086)
Open
Housing connectable (EF003088)
No
Suitable for rail mounting (EF003972)
No
Wall mounting possible (EF003973)
No
With integrated PCB-mounting connection system (EF003087)
No
Material (EF002169)
Other
Surface finishing (EF006569)
Other
Colour (EF000007)
Grey
RAL-number (EF000116)
7035

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 22,5-FP/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.