

INDUSTRIAL COMPONENT DATA

EH 35-C CS/ABS-PC GY7035 1069990 PHOENIX CONTACT DIN rail housing, Upper part, without connection opening, w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 35-C CS/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 35-C CS/ABS-PC GY7035
Catalog number	1069990
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-DAC503E4C7
Generated	2026-08-05

Product Overview

DIN rail housing, Upper part, without connection opening, width: 35.1 mm, height: 75 mm, depth: 36.95 mm, color: light gray (7035)

Rail box, Top of housing, tall design, no connection hole, width: 35.1 mm, height: 75 mm, depth: 36.95 mm, color: light gray (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1069990

Packing unit 1

GTIN 4055626747682

Custom tariff number 85389099

Drawings

Dimensions

Ambient conditions

General information

Standards and regulations

Item properties

Material data

[PCB data](#)

[Packaging information](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to topItem properties](#)

[Brief article description](#) Upper part of housing

Type EH 35-C CS/ABS-PC GY7035

Order No. 1069990

Housing type DIN rail housing

Housing series EH

Type Upper part

Max. IP code to attain IP20

Ventilation openings present no

[Back to topDimensions](#)

[Dimensional drawing](#)

Width [w] 35.1 mm

Height [h] 75 mm

Depth [d] 36.95 mm

[Back to topMaterial data](#)

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS-PC

[Back to topAmbient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 80 °C

Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)

[Back to topPCB data](#)

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

[Back to topGeneral information](#)

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

[Back to topPackaging information](#)

Pieces per package 10

Denomination packing units Pcs.

[Back to topStandards and regulations](#)

Flammability rating according to UL 94 V0

[Back to topClassifications](#)

eCl@ss

eCl@ss 4.0 27180401

eCl@ss 4.1 27180401

eCl@ss 5.0 27180506

eCl@ss 5.1 27180500

eCl@ss 6.0 271...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 35-C CS/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.