

INDUSTRIAL COMPONENT DATA

EH 45-C CS/ABS-PC GY7035 1069876 PHOENIX CONTACT DIN rail housing, Upper part, without connection opening, w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 45-C CS/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 45-C CS/ABS-PC GY7035
Catalog number	1069876
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-1EBD79B9F8
Generated	2026-08-03

Product Overview

DIN rail housing, Upper part, without connection opening, width: 45.1 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (7035)

Rail box, Top of housing, tall design, no connection hole, width: 45.1 mm, height: 75.26 mm, depth: 36.95 mm, colour: light grey (7035)

DIN rail housing, Upper housing part, tall design, no connection opening, width: 45.1 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (similar RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Upper housing part

Housing type DIN rail housing

Housing series EH

Product family EH..ABS-PC..

Type Upper housing part, tall design, no connection opening

Ventilation openings present no

Data management status

Article revision 00

DimensionsDimensional drawing

Width 45.1 mm
Height 75.26 mm
Depth 36.95 mm
Depth from base support surface 19.95 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
Housing material ABS-PC
Surface characteristics untreated
Environmental and real-life conditionsVibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60998-1:2002-12
Height of fall 50 cm
Frequency 10
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Half-sine
Acceleration 15g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Degree of protection (IP code)
Specific...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 45-C CS/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.