

## INDUSTRIAL COMPONENT DATA

# EH 67,5-B/ABS-PC BK9005 1069885 PHOENIX CONTACT DIN rail housing, Lower housing part with base latch, tall d..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 67,5-B/ABS-PC BK9005



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | EH 67,5-B/ABS-PC BK9005          |
| Catalog number  | 1069885                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-31E6D6234F                    |
| Generated       | 2026-08-05                       |

## Product Overview

DIN rail housing, Lower housing part with base latch, tall design, with vents, width: 67.6 mm, height: 75 mm, depth: 87.3 mm, color: black (9005)

Rail box, Bottom of housing with base anchorage, high design, with ventilation slits, width: 67.6 mm, height: 75 mm, depth: 87.3 mm, color: black (9005)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1069885

Packing unit 1

GTIN 4055626747651

Custom tariff number 85389099

Drawings

Dimensions

Ambient conditions

Mechanical strength/tumbling barrel

Shock

Test for assessing the risk of fire (glow wire)

General information

[Standards and regulations](#)

[Item properties](#)

[Material data](#)

[PCB data](#)

[Vibration test](#)

[Thermostability \(Ball Thrust Test\)](#)

[Degrees of protection provided by housings \(IP code\)](#)

[Packaging information](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to top](#)[Item properties](#)

[Brief article description](#) Mounting base housing

Type EH 67,5-B/ABS-PC BK9005

Order No. 1069885

Housing type DIN rail housing

Housing series EH

Type Lower housing part with base latch, tall design

Max. IP code to attain IP20

Mounting type DIN rail mounting/wall mounting (with optional base latch)

Ventilation openings present yes

[Back to top](#)[Dimensions](#)

[Dimensional drawing](#)

Width [ w ] 67.6 mm

Height [ h ] 75 mm

Depth [ d ] 87.3 mm

Depth from top edge of DIN rail to support point on upper part [ d ] 83 mm

[Back to top](#)[Material data](#)

Color (RAL) black (9005)

Flammability rating according to UL 94 V0

Housing material ABS-PC

[Back to top](#)[Ambient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 80 °C

Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)

[Back to top](#)[PCB data](#)

Number of PCB holders 7

PCB thickness 1.4 mm ... 1.8 mm

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latchi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 67,5-B/ABS-PC BK9005 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.