

INDUSTRIAL COMPONENT DATA

EH 67,5-C DS/ABS-PC GY7035 1069888 PHOENIX CONTACT DIN rail housing, Upper part, connection opening on both ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 67,5-C DS/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 67,5-C DS/ABS-PC GY7035
Catalog number	1069888
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-D03E888F46
Generated	2026-08-03

Product Overview

DIN rail housing, Upper part, connection opening on both sides, width: 67.6 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (7035)

Rail box, Top of housing, tall design, connection hole on both sides, connection hole on both sides, width: 67.6 mm, height: 75.26 mm, depth: 36.95 mm, color: light gray (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1069888

Packing unit 1

GTIN 4055626746845

Custom tariff number 85389099

Drawings

Dimensions

Ambient conditions

General information

Standards and regulations

Item properties

Material data

PCB data

Packaging information

Classifications

Drawings

Dimensional drawing

Back to topItem properties

Brief article description Upper part of housing

Type EH 67,5-C DS/ABS-PC GY7035

Order No. 1069888

Housing type DIN rail housing

Housing series EH

Type Upper part

Max. IP code to attain IP20

Mounting type Snap in

Ventilation openings present no

Back to topDimensions

Dimensional drawing

Width [w] 67.6 mm

Height [h] 75.26 mm

Depth [d] 36.95 mm

Depth from base support surface [d] 19.95 mm

Back to topMaterial data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS-PC

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 80 °C

Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)

Back to topPCB data

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

Back to topGeneral information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Back to topPackaging information

Pieces per package 10

Denomination packing units Pcs.

Back to topStandards and regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCI@ss

eCI@ss 4.0 27180401

eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 67,5-C DS/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.