

INDUSTRIAL COMPONENT DATA

EH 67,5 F-B/ABS-PC BK9005 1074951 PHOENIX CONTACT DIN rail housing, Lower housing part with base latch, flat..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 67,5 F-B/ABS-PC BK9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 67,5 F-B/ABS-PC BK9005
Catalog number	1074951
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-D8219AEF1F
Generated	2026-08-05

Product Overview

DIN rail housing, Lower housing part with base latch, flat design, width: 67.6 mm, height: 75 mm, depth: 30.3 mm, color: black (9005)

Rail box, Lower part of the housing with base anchorage, flat design, width: 67.6 mm, height: 75 mm, depth: 30.3 mm, color: black (9005)

DIN rail housing, Lower housing part with base latch, flat design, without vents, width: 67.6 mm, height: 75 mm, depth: 30.3 mm, color: black (similar RAL 9005), cross connection: without bus connector, number of positions cross connector: not relevant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Enclosure bottom part

Housing type DIN rail housing

Housing series EH

Product family EH..F..ABS-PC..

Type Lower housing parts without vents, housing cover necessary to complete the module

Max. number of positions 0)

Type Lower housing part with base latch, flat design

Ventilation openings present no

Data management status

Article revision 00

DimensionsDimensional drawing

Width 67.6 mm

Height 75 mm

Depth 30.3 mm

Depth from top edge of DIN rail to support point on upper part 26 mm

PCB design

PCB thickness 1.4 mm ... 1.8 mm

Material specificationsColor (Housing) black (RAL 9005)

Flammability rating according to UL 94 V0

Housing material ABS-PC

Surface characteristics untreated

Environmental and real-life conditionsVibration test

Specification IEC 60068-2-6:2007-12

Frequency 10 - 150 - 10 Hz

Sweep speed 1 octave/min

Amplitude 0.15 mm (10 Hz ... 58.1 Hz)

Acceleration 2g (58.1 Hz ... 150 Hz)

Test duration per axis 2.5 h

Test directions X-, Y- and Z-axis

Glow-wire test

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Thermal stability / ball thrust test

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20 N

Mechanical strength / tumbling barrel

Specification IEC 60998-1:2002-12

Height of fall 50 cm

Frequency 10

Shocks

Specification IEC 60068-2-27:2008-02

Pulse shape Half-sine

Acceleration 15g

Shock dura...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 67,5 F-B/ABS-PC BK9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.