

INDUSTRIAL COMPONENT DATA

EH 67,5 F-C DS/ABS-PC BK9005 1074945 PHOENIX CONTACT DIN rail housing, Upper part, connection opening on bot..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 67,5 F-C DS/ABS-PC BK9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 67,5 F-C DS/ABS-PC BK9005
Catalog number	1074945
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-BFF62068E4
Generated	2026-08-05

Product Overview

DIN rail housing, Upper part, connection opening on both sides, width: 67.6 mm, height: 74.65 mm, depth: 36.95 mm, color: black (9005)

Rail box, Top of housing, flat design, connection hole on both sides, width: 67.6 mm, height: 74.65 mm, depth: 36.95 mm, color: black (9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data
 Orderkey 1074945
 Packing unit 1
 GTIN 4055626777405
 Custom tariff number 85389099
 Drawings
 Dimensions
 Ambient conditions
 General information
 Standards and regulations
 Item properties
 Material data

PCB data

Packaging information

Classifications

Drawings

Dimensional drawing

[Back to top](#)Item properties

Brief article description Upper part of housing

Type EH 67,5 F-C DS/ABS-PC BK9005

Order No. 1074945

Housing type DIN rail housing

Housing series EH

Type Upper part

Max. IP code to attain IP20

Mounting type Snap in

Ventilation openings present no

[Back to top](#)Dimensions

Dimensional drawing

Width [w] 67.6 mm

Height [h] 74.65 mm

Depth [d] 36.95 mm

Depth from base support surface [d] 19.95 mm

[Back to top](#)Material data

Color (RAL) black (9005)

Flammability rating according to UL 94 V0

Housing material ABS-PC

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 80 °C

Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)

[Back to top](#)PCB data

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

[Back to top](#)General information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

[Back to top](#)Packaging information

Pieces per package 10

Denomination packing units Pcs.

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.0 27180506

eCl@s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 67,5 F-C DS/ABS-PC BK9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.