

INDUSTRIAL COMPONENT DATA

EH 70-C CS/ABS-PC GY7035 1071127 PHOENIX CONTACT DIN rail housing, Upper part, without connection opening, w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 70-C CS/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 70-C CS/ABS-PC GY7035
Catalog number	1071127
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-C2C1BF4357
Generated	2026-08-03

Product Overview

DIN rail housing, Upper part, without connection opening, width: 70.1 mm, height: 75 mm, depth: 36.95 mm, color: light gray (7035)

Rail box, Top, high design, no connection hole, width: 70.1 mm, height: 75 mm, depth: 36.95 mm, color: light grey (7035)

DIN rail housing, Upper housing part, tall design, no connection opening, width: 70.1 mm, height: 75 mm, depth: 36.95 mm, color: light gray (similar RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Upper housing part

Housing type DIN rail housing

Housing series EH

Product family EH..ABS-PC..

Type Upper housing part, tall design, no connection opening

Ventilation openings present no

Data management status

Article revision 00

DimensionsDimensional drawing

Width 70.1 mm

Height 75 mm
Depth 36.95 mm
Depth from base support surface 19.95 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
Housing material ABS-PC
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 80 °C
Relative humidity (storage/transport) 95 %
PCB dataType of PCB mount Latching
MountingMounting type Snap in
ETIM for 1071127 Low-voltage industrial controls and switchgear (EC002779)
Feature Name
Feature Value
Type of enclosure (EF003086)
Closed
Housing connectable (EF003088)
No
Suitable for rail mounting (EF003972)
No
Wall mounting possible (EF003973)
No
With integrated PCB-mounting connection system (EF003087)
No
Surface finishing (EF006569)
Other
Colour (EF000007)
Grey
RAL-number (EF000116)
7035
Width (EF000008)
70.1 mm
Height (EF000040)
75 mm
Depth (EF000049)
36.95 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 70-C CS/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.