

INDUSTRIAL COMPONENT DATA

EH 90-C CS/ABS-PC GY7035 1069919 PHOENIX CONTACT DIN rail housing, Upper part, without connection opening, w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 90-C CS/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 90-C CS/ABS-PC GY7035
Catalog number	1069919
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-0E047ADFF6
Generated	2026-08-05

Product Overview

DIN rail housing, Upper part, without connection opening, width: 90.1 mm, height: 75.27 mm, depth: 36.95 mm, color: light gray (7035)

Rail box, Top of housing, tall design, no connection hole, width: 90.1 mm, height: 75.27 mm, depth: 36.95 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1069919

Packing unit 1

GTIN 4055626747576

Custom tariff number 85389099

Drawings

Dimensions

Ambient conditions

General information

Standards and regulations

Item properties

Material data

[PCB data](#)

[Packaging information](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to topItem properties](#)

[Brief article description Upper part of housing](#)

Type EH 90-C CS/ABS-PC GY7035

Order No. 1069919

[Housing type DIN rail housing](#)

[Housing series EH](#)

[Type Upper part](#)

[Max. IP code to attain IP20](#)

[Mounting type Snap in](#)

[Ventilation openings present no](#)

[Back to topDimensions](#)

[Dimensional drawing](#)

Width [w] 90.1 mm

Height [h] 75.27 mm

Depth [d] 36.95 mm

[Back to topMaterial data](#)

[Color \(RAL\) light gray \(7035\)](#)

[Flammability rating according to UL 94 V0](#)

[Housing material ABS-PC](#)

[Back to topAmbient conditions](#)

[Ambient temperature \(storage/transport\) -40 °C ... 55 °C](#)

[Ambient temperature \(assembly\) -5 °C ... 80 °C](#)

[Ambient temperature \(operation\) -40 °C ... 80 °C \(depending on power dissipation\)](#)

[Back to topPCB data](#)

[Mounting position Vertical \(horizontal DIN rail\)](#)

[Type of PCB mount Latching](#)

[Back to topGeneral information](#)

[Type of note Assembly instruction:](#)

[Note Refer to the data sheet for the range in the download area.](#)

[Back to topPackaging information](#)

[Pieces per package 10](#)

[Denomination packing units Pcs.](#)

[Back to topStandards and regulations](#)

[Flammability rating according to UL 94 V0](#)

[Back to topClassifications](#)

[eCl@ss](#)

[eCl@ss 4.0 27180401](#)

[eCl@ss 4.1 27180401](#)

[eCl@ss 5.0 27180506](#)

[eCl@ss 5....](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 90-C CS/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.