

INDUSTRIAL COMPONENT DATA

ME MAX 6,2 SP 4-4 KMGY 2713104 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 6,2 SP 4-4 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 6,2 SP 4-4 KMGY
Catalog number	2713104
Category	Electronic enclosure
Minimum order	10 Pcs
Document ID	EO-6F6344E5D4
Generated	2026-08-02

Product Overview

Electronic housing

Rail housing, Complete housing, tall design, spring-loaded design, width: 6.3 mm, height: 93.1 mm, depth: 101.2 mm, colour: light grey (7035), cross bridge: without bus connector, number of poles cross connector: not relevant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 2713104

Packing unit 10 pc

Catalog page Page 683 (C-1-2013)

GTIN 4017918984786

Weight per Piece (excluding packing) 34.410 g

Custom tariff number 85369010

Country of origin DE (Germany)

Item properties

Brief article description Electronic housing

Type ME MAX 6,2 SP 4-4 KMGY

Order No. 2713104

Housing type Complete housing

Type Tall design

Max. IP code to attain IP20

Mounting type DIN rail mounting

Number of levels 4

Ventilation openings present no

Dimensions

Dimensional drawing

Width [w] 6.2 mm

Height [h] 93.1 mm

Depth [d] 102.5 mm

Depth from top edge of DIN rail [d] 95 mm

Material data

Color (RAL) light gray (7035)

Housing material PBT

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

PCB data

Number of PCB holders 1

Mounting position Vertical (horizontal DIN rail)

Power dissipation, single housing at 20 °C

Mounting position vertical

Power dissipation, single housing at 30 °C

Mounting position vertical

Power dissipation, single housing at 40 °C

Mounting position vertical

Power dissipation, single housing at 50 °C

Mounting position vertical

Power dissipation, single housing at 60 °C

Mounting position vertical

General information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Packaging inform...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 6,2 SP 4-4 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.