

**INDUSTRIAL COMPONENT DATA**

# UEGH 40/2 2757131 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UEGH 40/2



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | PHOENIX CONTACT      |
| MPN / Reference | UEGH 40/2            |
| Catalog number  | 2757131              |
| Category        | Electronic enclosure |
| Minimum order   | 10 Pcs               |
| Document ID     | EO-A5A7C655FA        |
| Generated       | 2026-08-01           |

## Product Overview

Electronic housing

Double-deck electronics housing fully equipped with 12 screw connections on each side for two printed circuit boards

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2757131

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 727 (C-1-2013)

GTIN 4017918104825

Weight per Piece (excluding packing) 119.210 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Housing type Complete housing

Housing material Polyamide (PA 6.6)

Color (RAL) green

Ambient conditions

Ambient temperature (operation) -40 °C ... 105 °C

**Dimensions**

Length 79 mm

Height 106.7 mm

Width 40 mm

Pitch 5 mm

Depth 79 mm

**Technical data**

Connection in acc. with standard CUL

Nominal voltage UN 300 V

Nominal current IN 10 A

AWG/kcmil 30-12

Indicator1 CUL1

Power dissipation without gap 6.1 W

Power dissipation with 20 mm gap 9.1 W

Number of positions 24

**Connection data**Conductor cross section solid min. 0.2 mm<sup>2</sup>Conductor cross section solid max. 4 mm<sup>2</sup>Conductor cross section flexible min. 0.2 mm<sup>2</sup>Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Stripping length 8 mm

**Standards and Regulations**

Connection in acc. with standard CUL

Flammability rating according to UL 94 V2

**Environmental Product Compliance**

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

**Classifications**

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss

7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ET...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / UEGH 40/2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.