

INDUSTRIAL COMPONENT DATA

UEGM 40/2 2792028 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UEGM 40/2



Manufacturer	PHOENIX CONTACT
MPN / Reference	UEGM 40/2
Catalog number	2792028
Category	Electronic enclosure
Minimum order	10 Pcs
Document ID	EO-CFE0A52B90
Generated	2026-08-03

Product Overview

Electronic housing

Electronics housing, fully equipped with 6 screw connections on each side, for two printed circuit boards

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2792028

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 725 (C-1-2013)

GTIN 4017918072537

Weight per Piece (excluding packing) 80.130 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Housing type Complete housing

Housing material Polyamide (PA 6.6)

Color (RAL) green

Ambient conditions

Ambient temperature (operation) -40 °C ... 105 °C

Dimensions

Length 79 mm

Height 85.5 mm

Width 40 mm

Pitch 5 mm

Depth 79 mm

Technical data

Connection in acc. with standard CUL

Nominal voltage UN 300 V

Nominal current IN 10 A

AWG/kcmil 30-12

Indicator1 CUL1

Power dissipation without gap 5.2 W

Power dissipation with 20 mm gap 11.2 W

Number of positions 12

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 4 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Stripping length 8 mm

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss

7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UEGM 40/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.