

INDUSTRIAL COMPONENT DATA

ELR H5-I-PT-24DC/500AC-2-L 1199926 PHOENIX CONTACT

Hybrid motor starter, 3~AC motor reversal up to 550V AC/2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ELR H5-I-PT-24DC/500AC-2-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	ELR H5-I-PT-24DC/500AC-2-L
Catalog number	1199926
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-AA49BFFEA5
Generated	2026-08-06

Product Overview

Hybrid motor starter, 3~AC motor reversal up to 550V AC/2.4A, 24V DC input, class 10 trip characteristic, overload function, no symmetry supervision and no phase fault detection and underload. Possibility of connecting single-phase motors.

Hybrid motor starter, 3~AC motor inversion up to 550 V AC/2.4 A, 24 V DC input, class 10 trigger feature, overload function, no symmetry monitoring and no phase and underload failure detection. Possibility of connection of single-phase motors.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

ETIM for 1199926 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Type of motor starter (EF009598)

Reversing starter

With short-circuit release (EF006691)

No

Rated control supply voltage DC (EF003980)

19.2 V

Voltage type for actuating (EF008242)

DC

Rated operation current Ie (EF001443)

2.4 A
Rated operation current at AC-3, 400 V (EF009602)
2.4 A
Overload release current setting (EF002336)
0.18 A
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as normally closed contact (EF001377)
0
Temperature compensated overload protection (EF009604)
No
Release class (EF006668)
CLASS 10
Type of electrical connection of main circuit (EF006819)
Spring clamp connection
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Spring clamp connection
Suitable for rail mounting (EF003972)
Yes
Number of command positions (EF001372)
1
External reset possible (EF003426)
Yes
Degree of protection (IP) (EF005474)
IP20
Width (EF000008)
22.5 mm
Height (EF000040)
107.5 mm
Depth (EF000049)
114 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ELR H5-I-PT-24DC/500AC-2-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.