

INDUSTRIAL COMPONENT DATA

ELR H5-I-PT- 24DC/500AC-9-P 2909560 PHOENIX CONTACT

Hybrid motor starter as an alternative to a conventional..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ELR H5-I-PT-24DC/500AC-9-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	ELR H5-I-PT-24DC/500AC-9-P
Catalog number	2909560
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-E1E6F70B95
Generated	2026-08-06

Product Overview

Hybrid motor starter as an alternative to a conventional reversing contactor. Reverses 3~ AC motors up to 9 A and offers motor protection. Possible supply and relay extension via DIN rail connector.

Hybrid motor starter as an alternative to the classic inverter contactor circuit. Reverses motors from 3~ AC up to 9 A and offers protection for the motor. Possibility of feeding and expanding relays by means of rail bus connectors.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2909560

Packing unit 1 pc

Catalog page Page 27 (C-5-2019)

GTIN 4055626406602

Weight per Piece (excluding packing) 300.000 g

Custom tariff number 85371098

Country of origin DE (Germany)

Drawings

Ambient conditions

Input data

Output data reply output

General

Connection data 2

Standards and Regulations

UL data

Classifications

Dimensions

Device supply

Output data load output

Overspeed tripping

Connection data

Insulation characteristics

Conformance/approvals

Environmental Product Compliance

Drawings

Block diagram

Back to topDimensions

Width 22.5 mm

Height 107.5 mm

Depth 114 mm

Back to topAmbient conditions

Ambient temperature (operation) -25 °C ... 70 °C (observe derating)

Ambient temperature (storage/transport) -40 °C ... 80 °C

Maximum altitude ≤ 2000 m

Degree of protection IP20

Back to topDevice supply

Rated control circuit supply voltage US 24 V DC

Control supply voltage range 19.2 V DC ... 30 V DC

Rated control supply current IS 60 mA

Type of protection Surge protection

Reverse polarity protection

Back to topInput data

Input name Control input right/left

Rated actuating voltage UC 24 V DC

Triggering voltage range 19.2 V DC ... 30 V DC

Rated actuating current IC 7 mA

Switching threshold 9.6 V ("0" signal)

19.2 V ("1" signal)

Typical turn-off time < 30 ms

Type of protection Reverse polarity protection

Back to topOutput data load output

Output name AC output

Rated operating voltage Ue 500 V AC

Operating voltage range 42 V AC ... 550 V AC

Rated operat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ELR H5-I-PT-24DC/500AC-9-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.