

INDUSTRIAL COMPONENT DATA

EM-2RPT/21AU-R/L-P 2909573 PHOENIX CONTACT Relay extension module for ELR-...-P hybrid motor starters, feedb..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EM-2RPT/21AU-R/L-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	EM-2RPT/21AU-R/L-P
Catalog number	2909573
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-984829BA31
Generated	2026-08-05

Product Overview

Relay extension module for ELR-...-P hybrid motor starters, feedback of forward and reverse running when control signal is present, Push-in connection, DIN rail connector included

Expansion module relay for ELR-...-P hybrid motor starter, left and right drive response with control signal and push-in connection, rail bus connector included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2909573

Packing unit 1 pc

Catalog page Page 26 (C-5-2019)

GTIN 4055626445489

Weight per Piece (excluding packing) 180.000 g

Custom tariff number 85364190

Country of origin DE (Germany)

Drawings

Output data

Dimensions

Environmental Product Compliance

[General](#)[Connection data, output side](#)[Standards and Regulations](#)[Classifications](#)[Drawings](#)[Circuit diagram](#)[Back to top](#)[General](#)[Mounting position Vertical \(horizontal DIN rail\)](#)[Mounting type DIN rail mounting](#)[Assembly instructions In rows with zero spacing](#)[Ambient temperature \(operation\) -25 °C ... 70 °C](#)[Ambient temperature \(storage/transport\) -40 °C ... 80 °C](#)[Back to top](#)[Output data](#)[Contact type 1 PDT](#)[Rated operating voltage Ue 24 V DC](#)[230 V AC](#)[Switching capacity according to IEC 60947-5-1 3 A \(230 V, AC15\)](#)[2 A \(24 V, DC13\)](#)[Back to top](#)[Connection data, output side](#)[Connection name Load circuit](#)[Connection method Push-in connection](#)[Stripping length 10 mm](#)[Conductor cross section solid 0.2 mm² ... 2.5 mm²](#)[Conductor cross section flexible 0.2 mm² ... 2.5 mm²](#)[Conductor cross section AWG 24 ... 14](#)[Back to top](#)[Dimensions](#)[Width 22.50 mm](#)[Height 106.60 mm](#)[Depth 113.70 mm](#)[Back to top](#)[Standards and Regulations](#)[Standards/regulations IEC 60947-5-1](#)[Back to top](#)[Environmental Product Compliance](#)[China RoHS Environmentally Friendly Use Period = 50](#)[For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"](#)[Back to top](#)[Classifications](#)[eCl@ss](#)[eCl@ss 5.0 27371600](#)[eCl@ss 5.1 27371600](#)[eCl@ss 6.0 2...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EM-2RPT/21AU-R/L-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.