

INDUSTRIAL COMPONENT DATA

EM-DUO 250/15 5602630 PHOENIX CONTACT Double plug socket to mount on a rail with two female connectors 250 V..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EM-DUO 250/15



Manufacturer	PHOENIX CONTACT
MPN / Reference	EM-DUO 250/15
Catalog number	5602630
Category	Socket outlet for distribution board
Minimum order	1 Pcs
Document ID	EO-080ED794B4
Generated	2026-08-05

Product Overview

Double plug socket to mount on a rail with two female connectors 250 V AC/15 A for mounting on a rail of 35 mm according to en 60715. For enhanced safety, the grounding prong is at the top, thereby avoiding short circuits between the tabs in the conductive and non-conductive voltage. Housing Color: ivory. National variant: USA Type of connection: connection by screw.

Dual rail mounting socket with two 250 V AC/15 A female connectors for mounting on a 35 mm rail according to EN 60715. For added safety, the ground plug is located at the top, preventing short circuits between the conductive and non-conductive reeds. Shell color: ivory. National variant: USA. Connection type: screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Data commercial

Key order Five million six hundred two thousand six hundred thirty

Packing unit 1 pcs

Key selling BG4613 -

EAN Four trillion forty six billion three hundred fifty six million six hundred eighty four thousand four hundred eight

Unit weight (excluding packaging) 290,300 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin US (united States)

Measures

Width 82 mm

Height 135 mm

Depth 49 mm

Environmental conditions

Room temperature (service) -35 °C ... 60 °C

Overview

Rated voltage UN 250 V AC

Nominal current IN 15 To

You can use the form specific to the country in USA

Canada

Mexico

Bahamas

Bermuda

Columbia

Costa Rica

Ecuador

El Salvador

Panama

Puerto Rico

Taiwan

Venezuela

Virgin Islands

Color ivory

Isolation Polycarbonate & ABS blend

Standards/specifications CSA 22.2

Data connection

Section of conductor rigid max. 6 mm²

Section of flexible conductor max. 4 mm²

Section of conductor AWG max. Ten

Type of connection Connection by screw

Length desaislar 8 mm

Screw thread M3

Standards and specifications

Standards/specifications CSA 22.2

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Space of time for the intended use (FEUP): 50 years

You will find information about hazardous substances in the manufacturer's declaration in the "Downloads" tab

Ratings

eCl@ss 4.0 Twenty seven million two hundred fifty thousand three hundred thirteeneCl@ss 4.1 Twenty seven million two hundred fifty thousand thre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EM-DUO 250/15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.