

INDUSTRIAL COMPONENT DATA

EM-DUO120/20/GFI/AUX/NO 5602192 PHOENIX CONTACT

Outlet mounting on a rail for 120 V AC/20 A, with terminals ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EM-DUO120/20/GFI/AUX/NO



Manufacturer	PHOENIX CONTACT
MPN / Reference	EM-DUO120/20/GFI/AUX/NO
Catalog number	5602192
Category	Socket outlet for distribution board
Minimum order	1 Pcs
Document ID	EO-CFA52C8820
Generated	2026-08-06

Product Overview

Outlet mounting on a rail for 120 V AC/20 A, with terminals and additional switch of protection against leakage currents (RCCB/GFCI) mounting rail 35 mm according to en 60715. The switches of protection against leakage currents to protect against electrical accidents related to ground connections. For enhanced safety, the grounding prong is at the top, thereby avoiding short circuits between the tabs in the conductive and non-conductive voltage. Housing Color: white. National variant: USA Type of connection: connection by screw.

DIN rail mountable residual current switch (GFCI) for 35 mm DIN rail in accordance with EN 60715. Residual current circuit breakers protect against electrical accidents related to ground defects. For high safety, the ground pin is located at the top to prevent short circuits between the conductive and non-voltage-conducting tabs. Shell color: white. Country variant: USA Connection type: screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

Additional Product Information

Commercial data
Order key 5602192
Packaging unit 1 pcs
Sell key BG4613 -
Ean 4046356126236
Weight per unit (excluding packaging) 307,300 g
Tariff rate number 85366990

Country of origin US (United States)

Measurement

Width 82 mm

Height 135 mm

Depth 49 mm

Environmental conditions

Ambient Temperature (Service) -35 °C ... 60 °C

General

Nominal voltage UN 125 V AC

Nominal Current IN 20 A

It can be used in the country-specific way in USED

Canada

Mexico

Bahamas

Bermuda

Columbia

Costa Rica

Ecuador

El Salvador

Panama

Puerto Rico

Taiwan

Venezuela

Virgin Islands

Colour ivory

Isolation Polycarbonate & ABS blend

Standards/Specifications UL 508

CSA 22.2

Response Time 25 ms (6 mA)

Connection data

Max. rigid conductor section 6 mm²

Max. flexible conductor section 4 mm²

Conductor section AWG max. 10

Connection type Screw connection

Length to be de-insulated 8 mm

Screw thread M3

Standards & Specifications

Standards/Specifications UL 508

CSA 22.2

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Time Span for Intended Use (EFUP): 50 years

You can find information about hazardous substances in the manufacturer's declaration under the "Downloads" tab

Classifications

eCl@ss 4.027142305eCl@ss 4.127142305eCl@ss 5.027143412eCl@ss 5.127142300eCl@ss 6.027142300eCl@ss
7.027142305eCl@ss 8.027142305eCl@ss 9.027142305

ETIM 2.0EC001325ETIM 3.0EC001325ETIM 4.0EC001663ETIM 5.0EC001663ETIM 6.0EC001663

UNSPSC 6.0130211806UNSPSC 7.090139121406UNSPSC 1139121406UNSPSC 12.0139121406UNSPSC 13.23...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EM-DUO120/20/GFI/AUX/NO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.